

ecm's webbed site

2020 by C. Masloch. Usage of the works is permitted provided that this instrument is retained with the works, so that any entity that uses the works is notified of this instrument. **DISCLAIMER: THE WORKS ARE WITHOUT WARRANTY.**

This document has been compiled on 2022-12-29.

Contents

Section 1: News	4
Section 2: Projects	6
2.1 IDebug debugger	6
2.2 TracList - Trace debugging output in listing files	6
2.3 RxDOS 7.2x kernel	6
2.4 IDOS boot loaders	6
2.5 86 Mode NASM macro collection	6
2.6 NASM 2.05 based x86 Instruction Reference	7
2.7 ACEGALS - Assembly Comments Explained: Guide for Advanced Learning and Style	7
2.8 Boot image FAT FS formatting script	7
2.9 Terminate and Stay Resident (TSR) programs	7
2.9.1 KEEPHOOK utility	7
2.9.2 RxANSI - ANSI and LESS sequence parser	7
2.9.3 IClock - Clock display TSR	7
2.9.4 SEEKEXT - Seek service extension	7
2.9.5 FDAPM - A tool for APM power management and energy saving	8
2.9.6 TSR example	8
2.9.7 Tools to work with TSR programs	8
2.9.7.1 SHUFHOOK utility	8
2.9.7.2 RENUMBER	8
2.9.7.3 AMITSRS - List resident AMIS multiplexers	8
2.10 Other builds	8
Section 3: Links	9

3.1 The pushbx blog	10
Section 4: What is "pushbx"?	11
Source format of this page	12
Source Control Revision ID	13

Section 1: News

2022-12-23 Dec Fri

booting now allows to cut out boot loader parts from a given file, as well as fragmenting files preloaded into the image

2022-08-06 Aug Sat

Added ICDebug build to the current releases that are created automatically. The new conditionally debuggable build option has also been covered by a blog post.

2022-07-20 Jul Wed

Added Eric Auer's Terminal and the Insight debugger to the current releases that are created automatically.

2022-07-12 Jul Tue

Updated the NASM revision that's used for building current releases. Now line numbers of included files are correct in listings as well as in the assembler's messages.

2022-07-10 Jul Sun

IDebug symbolic branch merged into default branch, made a build option that is default off. (As announced on the blog.)

2022-04-24 Apr Sun

The new pushbx blog is officially online

2022-03-08 Mar Tue

IDebug release 4

2021-11-04 Nov Thu

IDebug current release of DDebug added

2021-11-02 Nov Tue

Other builds added (FreeDOS kernel and its SHARE for now)

2021-11-01 Nov Mon

KEEPHOOK got a fix to a bug that made for a few broken releases

2021-10-30 Oct Sat

RENUMBER added

AMITSRS listed

2021-10-26 Oct Tue

FDAPM added

2021-10-24 Oct Sun

TSRs changed to use Update IISP Header function as now provided by IDebug's AMIS interface

IDebug current release file added

2021-10-19 Oct Tue

SHUFHOOK first release added

2021-10-13 Oct Wed

RxANSI listed

IClock listed

SEEKEXT listed

TSR example listed

TSR current releases added

2021-10-12 Oct Tue

KEEPHOOK first release added

2021-08-15 Aug Sun

IDebug release 3

2021-05-17 May Mon

Moved from ulukai.org to pushbx.org domain

2021-05-05 May Wed

IDebug release 2

2021-04-07 Apr Wed

The IDebug manual had a News chapter added

2021-02-18 Feb Thu

What is "pushbx"?

2021-02-15 Feb Mon

IDebug release 1

Section 2: Projects

2.1 IDebug debugger

IDebug is a 86-DOS debugger based on the MS-DOS Debug clone FreeDOS Debug. It features DPMI client support for 32-bit and 16-bit segments, a 686-level assembler and disassembler, an expression evaluator, an InDOS and a bootloaded mode, script file reading, serial port I/O, permanent breakpoints, conditional tracing, buffered tracing, and auto-repetition of some commands. There is also a symbolic debugging branch being developed.

The manual (text, PDF) is available online. The repo is hosted at <https://hg.pushbx.org/ecm/ldebug/> and proper releases are available at <https://pushbx.org/ecm/download/ldebug/>. A current release is available at <https://pushbx.org/ecm/download/ldebug.zip> and a current release of the debuggable debugger is available at <https://pushbx.org/ecm/download/lddebug.zip> (You only need this one if you want to debug the debugger itself.) Further, a current release of the conditionally debuggable debugger is available at <https://pushbx.org/ecm/download/lcdebug.zip> (This one can switch debuggable mode off and on.)

2.2 TracList - Trace debugging output in listing files

A companion application to IDebug, connecting to the debugger's serial I/O. It traces execution through NASM format listing files. The manual (text, PDF) is available online. The repo is hosted at <https://hg.pushbx.org/ecm/tracetest/>

2.3 RxDOS 7.2x kernel

RxDOS is an alternative DOS kernel. It is not yet ready for general use. Unlike the FreeDOS kernel, its source is entirely in assembly language. (As of RxDOS 7.20N the source has been ported from MASM to NASM.) Unlike DR-DOS, MS-DOS, and PC-DOS it is (copylefted) free software. It aims to support extended features such as FAT32, LFNs, and LBA. It already supports UMBs (for DOSDATA, DOSCODE) and the HMA (for DOSCODE). Support for additional extensions is planned, such as FAT+, cluster sizes exceeding 32 KiB, sector sizes up to 8 KiB, and moving many DOS data structures into the UMA and HMA. The repo is hosted at <https://hg.pushbx.org/ecm/rxdos-7.2x/>

2.4 IDOS boot loaders

Advanced boot loading stages used by kernels or other bootloaded programs. The repos are hosted at <https://hg.pushbx.org/ecm/ldosboot/> and <https://hg.pushbx.org/ecm/ldosmbr/>

2.5 86 Mode NASM macro collection

A macro collection featuring parts such as defaultable defines for conditional assembly, stack frame calculation, anonymous @@ labels, safer sectioning directives, and assisted flag bit

accesses. The repo is hosted at <https://hg.pushbx.org/ecm/lmacros/>

2.6 NASM 2.05 based x86 Instruction Reference

An assembly language reference covering all general instructions up to a 686-level instruction set. Includes encoding schemes and some general English-language descriptions. It is available online here (text, PDF). The repo is hosted at <https://hg.pushbx.org/ecm/insref/>

2.7 ACEGALS - Assembly Comments Explained: Guide for Advanced Learning and Style

A reference guide for our assembly comments and formatting styles. It is available online here (text, PDF). The repo is hosted at <https://hg.pushbx.org/ecm/acegals/>

2.8 Boot image FAT FS formatting script

A NASM script that allows formatting an image file with FAT12, FAT16, or FAT32. The filesystem can be preloaded with files. Both diskette or harddisk images can be created. Optionally an MBR and a dosemu image header can be wrapped around the image. For FAT32 a backup boot sector copy and an FSINFO sector can be initialised. Sector sizes between 32 Bytes and 8 KiB are supported. Likewise cluster sizes between 1 to 256 sectors. (Minimum cluster size is 32 Bytes, maximum is 2 MiB.) The repo is hosted at <https://hg.pushbx.org/ecm/bootimg/>

2.9 Terminate and Stay Resident (TSR) programs

The current releases are created automatically from the repos and are updated daily. Old files of the current releases are found at <https://pushbx.org/ecm/download/old/>

2.9.1 KEEPHOOK utility

A TSR which aids the uninstalling of other TSRs. The manual (text, PDF) is available online. The repo is hosted at <https://hg.pushbx.org/ecm/keephook/> and a current release is available at <https://pushbx.org/ecm/download/keephook.zip>

2.9.2 RxANSI - ANSI and LESS sequence parser

RxANSI is a TSR to take over interrupt 29h and parse ANSI and LESS sequences. It only affects output - it does not do any input. The repo is hosted at <https://hg.pushbx.org/ecm/rxansi/> and some releases are available at <https://pushbx.org/ecm/download/> and a current release is available at <https://pushbx.org/ecm/download/rxansi.zip>

2.9.3 IClock - Clock display TSR

IClock is a TSR that continuously displays a clock in the upper right-side corner of the screen by writing to the text mode video buffer. It can be customised using build time options. The repo is hosted at <https://hg.pushbx.org/ecm/lclock/> and a current release is available at <https://pushbx.org/ecm/download/lclock.zip>

2.9.4 SEEKEXT - Seek service extension

This TSR extends DOS with an interrupt 21h handler. It hooks the services 21.42 (short seek) and 21.7142 (long seek). The short seek hook is to provide sensible results from positive or negative 32-bit seek offsets for file handles that implement long seek (21.7142). The

long seek hook is to redirect calls to the special int 2F.1142 redirector long seek interface, which is used by recent dosemu2 to provide 64-bit seeking on its redirected file systems. The repo is hosted at <https://hg.pushbx.org/ecm/seekext/> and a current release is available at <https://pushbx.org/ecm/download/seekext.zip>

2.9.5 FDAPM - A tool for APM power management and energy saving

The power savings utility for FreeDOS, originally by Eric Auer. Extended to use IISP headers, an AMIS multiplexer, and to provide the UNLOAD command, with the advanced deinstallation method. The repo is hosted at <https://hg.pushbx.org/ecm/fdapm/> and a current release is available at <https://pushbx.org/ecm/download/fdapm.zip>

2.9.6 TSR example

This project is an example of a TSR. It was originally based on RxANSI, and was in turn the base for IClock, SEEKEXT, and KEEPHOOK. It implements an AMIS multiplexer and features optimal installation and the advanced deinstallation method. The repo is hosted at <https://hg.pushbx.org/ecm/tsr/> (No releases are going to be provided because this is useful only for developers.)

2.9.7 Tools to work with TSR programs

2.9.7.1 SHUFHOOK utility

This tool allows to re-order interrupt handlers. The manual (text, PDF) is available online. The repo is hosted at <https://hg.pushbx.org/ecm/shufhook/> and a current release is available at <https://pushbx.org/ecm/download/shufhook.zip>

2.9.7.2 RENUMBER

This tool allows to change the AMIS multiplex numbers of resident multiplexers. The repo is hosted at <https://hg.pushbx.org/ecm/renumber/> and a current release is available at <https://pushbx.org/ecm/download/renumber.zip>

2.9.7.3 AMITSRS - List resident AMIS multiplexers

This tool lists AMIS multiplexers that are resident. It is based on the tool of the same name that was released to the Public Domain by Ralf Brown in 1992. The verbose mode has been extended to list the multiplex number and interrupt list of each resident multiplexer. It has also been updated to compile with the ia16 gcc and libi86. The repo is hosted at <https://hg.pushbx.org/ecm/amitsrs/> and a current release is available at <https://pushbx.org/ecm/download/amitsrs.zip>

2.10 Other builds

The current release scripts got updated to build a few projects that are kept in git repos. These are <https://pushbx.org/ecm/download/fdkernel.zip> (from repo at <https://github.com/fdos/kernel.git>) and <https://pushbx.org/ecm/download/fdshare.zip> (from repo at <https://github.com/fdos/share.git>) and <https://pushbx.org/ecm/download/freecom.zip> (from repo at <https://github.com/fdos/freecom.git>) (While these contain some contributions by me, I do not host current repos of them anywhere.)

Note: fdkernel builds after the 2021-11-23 release and before the 2022-04-06 release did not build correctly.

Section 3: Links

ecm's files

<https://pushbx.org/ecm/>

ecm's hgweb

<https://hg.pushbx.org/ecm/>

ecm's github

<https://github.com/ecm-pushbx/>

ecm's stackoverflow

<https://stackoverflow.com/users/738287/ecm?tab=profile>

ecm's NASM bug reports

https://bugzilla.nasm.us/buglist.cgi?f1=reporter&list_id=1912&o1=equals&v1=pushbx%40ulukai.org

ecm's twitter

<https://twitter.com/pushbx/>

BTTR Software

<https://www.bttr-software.de/>

DOS ain't dead

<https://www.bttr-software.de/forum/>

3.1 The pushbx blog

Longer form comments or explanations can now go to the pushbx blog which runs on a dokuwiki instance on this server. It is expected that content that would be shared privately prior to this may land on there. That may include descriptions that do not fit into commit messages or are written later on with more hindsight. As of now (2022 April) this is experimental and may be used more or less frequently. Comments are generally enabled on individual blog pages. All comments are screened manually.

Section 4: What is "pushbx"?

The username 'pushbx' originates in Eric Auer's callver (public domain). A line there reads the instruction 'push bx' but has a comment that *also* reads 'push bx'. The reason? There's a line further down which has the instruction 'pop ax' with the comment 'but pop ax'. This hints at the fact that, to a beginner, it is unusual to push then pop with two different registers as the source and destination. I've been using pushbx as a username ever since at the latest 2012 March. **NEW:** The little used twitter account indicates that I have used the username pushbx as early as 2009-11-27 in the first tweet.

Source format of this page

This page has been created using the libre Halibut documentation preparation system.

Source Control Revision ID

hg 8592e5a22fa7, from commit on at 2022-12-29 23:56:01 +0100

If this is in ecm's repository, you can find it at
<https://hg.pushbx.org/ecm/webecm/rev/8592e5a22fa7>